



25-Ton Capacity Under-Axle Jack

Now includes
No. 220972 - 3 in.
lifting extension.



5012A
ANSI
PALD

Now includes
No. 220972 –
3" lifting
extension.



- Self-retracting, air-driven ram uses standard shop air. Release valve automatically applies air to retract ram.
- Low 8" minimum working height enables jack to get under any truck in the shop.
- Positioning jack is easy, even under vehicles with set-back axles, thanks to a 53" handle that locks into any of three positions, from vertical to horizontal.
- Maximum lift is 21" when used with the 3" lifting extension.
- Covered by the OTC Lifetime Marathon Warranty®. Exceeds ANSI PALD standards.

No. 5012A – Under-axle hydraulic jack with a 25-ton capacity, self-retracting ram. Includes No. 220972 – 3" lifting extension. Wt., 117 lbs.

No. 220972 – Lifting extension, included with No. 5012A, is 3" long and has a 1" diameter. Wt., 3 lbs., 4 oz.

No. 215009* – In-line oil lubricator. Add to air line to meter precise flow of lubricant to air motor. Has 1/4" NPT fitting. Wt., 8 oz.



215009

Specifications	5012A
Lifting range, screw retracted	8" min. height 13-1/8" max. height
Lifting range, screw extended	12-7/8" min. height 18" max. height
Cylinder stroke	5-1/8"
Extended screw length	4-7/8"
PSI range	100–200

***Not included, order separately. Prevents harmful contamination caused by moisture in the air line!**



1-800-533-6127
www.otctools.com